





Max load
300 kN



Recess
mounted




Joint width
20-150 mm




Movements
in 1 directions




Indoor/
outdoor



For joint ≤ 50 mm



For joint > 50 mm



Profile	Standard options ¹ (abc)	Sizes, mm			Layer thickness ² (mm)			Movements ³ , mm		Permissible loads (kN)		
		A	B	H	H _a	H _b	H _c	M _x	M _y ⁴			
SG 85/20-200/6	BB, HH, 33	20	190	6	3	—	3	30 (+15/-15)	—	300	70	20
SG 85/30-220/6		30	200	6	3	—	3	30 (+15/-15)	—	300	70	20
SG 85/50-230/6		50	220	6	3	—	3	30 (+15/-15)	—	300	70	20
SG 85/80-260/19	BBB, HHH, 333	80	260	10	3	4	3	30 (+15/-15)	—	300	70	15
SG 85/100-280/21		100	280	11	3	5	3	30 (+15/-15)	—	300	50	10
SG 85/120-320/23		120	320	11	3	5	3	30 (+15/-15)	—	300	50	10
SG 85/150-350/25		150	350	11	3	5	3	30 (+15/-15)	—	300	50	10

¹ The profile is made to order from different materials of the components of the profile layers a, b and c (see technical data):
 • B – Steel S235 with powder coating;
 • H – Steel S235 with hot dip galvanized;
 • 3 – Stainless steel 1.4301 (AISI 304)⁹

² Standard layer thicknesses are indicated. On request, the layers can be made in other thicknesses.
³ Standard movements limits are given. On request, the profile is produced with other movements limits - ask for data.
⁴ Vertical movements are not allowed.


▶ TECHNICAL DATA

Material⁹	S235 (1.0038)	AISI 304 (1.4301)
Strength, MPa	$\sigma_s=360-510$	$\sigma_s= 515$
Tolerances	EN 1090-2	
Length, m	3,0 ⁵	
Tooling	Mounting holes	
Fasteners	Included (Screws Rawlplug R-LX)	
Surface coat	• Powder ⁷ • Galvanized ⁸	Without coating

⁵ Profile length can be changed upon request.
⁶ The profile is supplied assembled, using mounting brackets, to the required width of the expansion joint. Kit includes RAWL-PLUG R-LX high strength concrete screws and DIN 7991 A2 stainless steel mounting screws.
⁷ Powder coated in any RAL color.
⁸ Hot dip galvanizing according to EN 1461.
⁹ The material of the layers can be changed to other types of steel: AISI 316, 321, 430, etc.

▶ EXECUTION OPTIONS

● ● Using a vapor barrier for waterproofing an expansion joint.



● ● Use of a fire barrier with a fire resistance rating of up

